

Technical data

HC 180i P



Compactors Series HC
Compactor with padfoot drum

H256

HIGHLIGHTS

- > High compaction performance
- > Spacious driver's platform with Easy Drive operating concept
- > Hammtronic for high comfort, safety and reduced emissions
- > Customised configuration possibilities and a wide range of options
- > Digital ready

TECHNICAL DATA HC 180i P (H256)

Weights

Operating weight with cab	kg lbs	17640 38,896
Operating weight with ROPS	kg lbs	17305 38,158
Empty weight without cab, without ROPS	kg lbs	16435 36,239
Max. operating weight	kg lbs	18390 40,550
Axle load, front/rear	kg lbs	11385/6255 25,104/13,792
Axle load for max. operating weight, front/rear	kg lbs	11410/6980 25,159/15,391
Static linear load, front	kg/cm lbs/in	53,20 297.9
French classification, value/class		75,37/VPM5
Wheel load per tire, rear	kg lbs	3127,5 6,896

Machine dimensions

Total length	mm in	6527 257.0
Total height with cab	mm in	3046 119.9
Total height with ROPS	mm in	3054 120.2
Height loading, min.	mm in	3046 119.9
Center distance	mm in	3267 128.6
Total width with cab	mm in	2474 97.4
Maximum working width	mm in	2140 84.3
Ground clearance, center	mm in	425 16.7
Curb clearance, left/right	mm in	462/462 18.2/18.2
Turning radius, inside	mm in	4137 162.9
Slope angle, front/rear	°	31,6/25,7

Drum dimensions

Drum width, front	mm in	2140 84.3
Drum diameter, front	mm in	1697 66.8
Drum thickness, front	mm in	30 1.2
Drum type, front		Padfoot
Height of the padfeet	mm in	112 4.4
Padfeet, quantity		130

Tire dimensions

Tire size, rear		TR 23.1/18-26 12 PR
-----------------	--	---------------------

Tire dimensions

Width over tires, rear	mm in	2140 84.3
Number of tires, rear		2

Diesel engine

Manufacturer		DEUTZ
Model		TCD 6.1 L6
Cylinders, quantity		6
Power ISO 14396, kW/PS/rpm		160,0/217,7/2000
Power SAE J1349, kW/HP/rpm		160,0/214,7/2000
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

Travel drive

Speed, infinitely variable	km/h mph	0 - 11,9 0.0 - 7.4
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	55/61

Vibration

Vibration frequency, front, I/II	Hz vpm	28/31 1,680/1,860
Amplitude, front, I/II	mm in	2,15/1,35 .085/.053
Centrifugal force, front, I/II	kN lbs	330/260 74,250/58,500

Steering

Swing angle +/-	°	max. 12
Steering, type		Articulated steering

Tank capacity/filling capacity

Fuel tank, capacity	L Gal	336 88.8
AdBlue/SCR reducing agent tank, capacity	L Gal	32 8.5

Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	104

EQUIPMENT

12 V sockets (double) | Two large exterior rear-view mirrors | 3-point articulation | Dashboard with displays, indicator lights and function keys | Easy Drive operating concept | ECO mode | Speed preselect | Hose protection on the front vehicle | Vibration-isolated driver's platform | Automatic vibration system | Traction Control, manual | Steel scraper, for padfoot drum

OPTIONAL EQUIPMENT