

Technical data

# HD+ 80i VV-HF



**Tandem rollers Series HD+**

Tandem roller with two vibrating roller drums

**H302**

**HIGHLIGHTS**

- > Operating concept Easy Drive
- > 3-point articulation for even weight distribution and excellent directional stability
- > Innovative cabin concept for optimal visibility and high comfort
- > Seat-operating unit can be moved and rotated
- > Digital ready

**TECHNICAL DATA HD+ 80i VV-HF (H302)**

**Weights**

Operating weight with cab	kg lbs	7795 17,188
Operating weight with ROPS	kg lbs	7615 16,791
Empty weight without cab, without ROPS	kg lbs	6900 15,214
Max. operating weight	kg lbs	10400 22,932
Axle load, front/rear	kg lbs	3930/3865 8,666/8,522
Static linear load, front/rear	kg/cm lbs/in	23,39/23,01 131.0/128.9
French classification, value/class		17,03/VT0

**Machine dimensions**

Total length	mm in	4480 176.4
Total height with cab	mm in	2890 113.8
Total height with ROPS	mm in	2970 116.9
Height loading, min.	mm in	2080 81.9
Center distance	mm in	3340 131.5
Total width with cab	mm in	1800 70.9
Maximum working width	mm in	1815 71.5
Ground clearance, center	mm in	340 13.4
Curb clearance, left/right	mm in	750/750 29.5/29.5
Turning radius, inside	mm in	4140 163.0

**Drum dimensions**

Drum width, front/rear	mm in	1680/1680 66.1/66.1
Drum diameter, front/rear	mm in	1140/1140 44.9/44.9
Drum thickness, front/rear	mm in	17/17 0.7/0.7
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	135 5.3

**Diesel engine**

Manufacturer		DEUTZ
Model		TCD 2.9 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		55,4/75,3/2300
Power SAE J1349, kW/HP/rpm		55,4/74,2/2300
Exhaust emission standard		EU Stage V / EPA Tier 4

**Diesel engine**

Exhaust gas after-treatment		DOC-DPF
-----------------------------	--	---------

**Travel drive**

Speed, infinitely variable	km/h mph	0 - 9,7 0.0 - 6.0
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	41/45

**Vibration**

Vibration frequency, front, level I/II	Hz vpm	45/67 2,700/4,020
Vibration frequency, rear, level I/II	Hz vpm	45/67 2,700/4,020
Amplitude, front, level I/II	mm in	0,55/0,30 .022/.012
Amplitude, rear, level I/II	mm in	0,55/0,30 .022/.012
Centrifugal force, front, level I/II	kN lbs	70/85 15,750/19,125
Centrifugal force, rear, level I/II	kN lbs	70/85 15,750/19,125

**Steering**

Pendulum angle +/-	°	10
Steering, type		Articulated steering

**Water-sprinkling system**

Water sprinkling, type		Pressure
------------------------	--	----------

**Tank capacity/filling capacity**

Fuel tank, capacity	L Gal	120 31.7
Water tank, capacity	L Gal	700 184.9

**Sound level**

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

**EQUIPMENT**

Dashboard tiltable | Pressure water sprinkling system | ECO mode | Speed preselect | Vibration-insulated driver's platform | Track offset, hydraulic | Water filter system (3-fold) | Central water outlet

**OPTIONAL EQUIPMENT**

Heating and air-conditioning system | Steering column with comfort exit and tiltable dashboard | Tachograph | Bluetooth interface for Smart Doc | Smart Compact | Protective roof | Edge pressing and cutting equipment | HAMM Compaction Meter (HCM) | HAMM Temperature Meter (HTM) | JDLink | Working spotlights | Rotating beacon