

Technical data

# HD 13i VV



## Tandem rollers Series HD CompactLine

Tandem roller with two vibrating roller drums

H285

### HIGHLIGHTS

- > Simple transport, simple loading
- > Simple, intuitive and language-neutral control
- > Ergonomic driver platform
- > Excellent view of drum edge, machine and construction site environment
- > Compact dimensions

**TECHNICAL DATA HD 13i VV (H285)**

**Weights**

Operating weight with cab	kg lbs	4415 9,735
Operating weight with ROPS	kg lbs	4165 9,184
Empty weight without cab, without ROPS	kg lbs	3845 8,478
Maximum operating weight	kg lbs	5360 11,819
Axle load, front/rear	kg lbs	2120/2045 4,675/4,509
Static linear load, front/rear	kg/cm lbs/in	16,3/15,7 91.3/87.9
French classification, value/class		11,1/VT0

**Machine dimensions**

Total length	mm in	2965 116.7
Total height with cab	mm in	2720 107.1
Total height with ROPS	mm in	2590 102.0
Height loading, min.	mm in	1820 71.7
Total length with cab	mm in	2977 117.2
Center distance	mm in	1950 76.8
Center distance with cab	mm in	1960 77.2
Total width	mm in	1426 56.1
Maximum working width	mm in	1350 53.1
Ground clearance, center	mm in	305 12.0
Curb clearance, left/right	mm in	720/720 28.3/28.3
Turning radius, inside	mm in	2690 105.9

**Drum dimensions**

Drum width, front/rear	mm in	1300/1300 51.2/51.2
Drum diameter, front/rear	mm in	900/900 35.4/35.4
Drum thickness, front/rear	mm in	17/17 0.7/0.7
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	0/50 0.0/2.0

**Diesel engine**

Manufacturer		Kubota
Model		V2403-CR-ESB
Cylinders, quantity		4

**Diesel engine**

Power ISO 14396, kW/PS/rpm		36,8/50,0/2700
Power SAE J1995, kW/HP/rpm		37,4/50,1/2700
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF

**Travel drive**

Speed, infinitely variable	km/h mph	0 - 11,0 0.0 - 6.8
Gradeability, with/without vibration	%	30/40

**Vibration**

Vibration frequency, front, I/II	Hz vpm	60/51 3,600/3,060
Vibration frequency, rear, I/II	Hz vpm	60/51 3,600/3,060
Amplitude, front, I/II	mm in	0,51/0,31 .020/.012
Amplitude, rear, I/II	mm in	0,51/0,31 .020/.012
Centrifugal force, front, I/II	kN lbs	64/39 14,400/8,775
Centrifugal force, rear, I/II	kN lbs	64/39 14,400/8,775

**Steering**

Pendulum angle +/-	°	8
Steering, type		Articulated steering

**Water-sprinkling system**

Water sprinkling, type		Pressure
------------------------	--	----------

**Tank capacity/filling capacity**

Fuel tank, capacity	L Gal	73 19.3
Water tank, capacity	L Gal	285 75.3

**Sound level**

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	103

**EQUIPMENT**

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling system | Driver's platform with access from both sides | Drive lever, left and right | V-belt protection | Mechanical battery isolation switch | Track offset, mechanical | Automatic vibration system | Water filter system (3-fold) | Central water outlet | CompactLine front towing eye

**OPTIONAL EQUIPMENT**