

Technical data

# HX 90i VV



## Tandem rollers Series HX

Tandem roller with two vibrating roller drums

H299

### HIGHLIGHTS

- > High compaction performance due to optimal setting of the compaction parameters
- > Intelligent water sprinkler system
- > Operating concept Easy Drive
- > Innovative cabin concept for optimal visibility and high comfort
- > Digital ready

## TECHNICAL DATA HX 90i VV (H299)

## Weights

Operating weight with cab	kg lbs	9315 20,540
Empty weight without cab, without ROPS	kg lbs	8220 18,125
Max. operating weight	kg lbs	11930 26,306
Axle load, front/rear	kg lbs	4270/4595 9,415/10,132
Axle load for max. operating weight, front/rear	kg lbs	4290/7640 9,459/16,846
Static linear load, front/rear	kg/cm lbs/in	28,08/27,34 157.2/153.1
French classification, value/class		22,7/VT1

## Machine dimensions

Total length	mm in	4448 175.1
Total height with cab	mm in	2965 116.7
Height loading, min.	mm in	2170 85.4
Center distance	mm in	3250 128.0
Total width with cab	mm in	1860 73.2
Maximum working width	mm in	3050 120.1
Ground clearance, center	mm in	300 11.8
Curb clearance, left/right	mm in	655/655 25.8/25.8
Turning radius, inside	mm in	3000 118.1

## Drum dimensions

Drum width, front/rear	mm in	1680/1680 66.1/66.1
Drum diameter, front/rear	mm in	1200/1200 47.2/47.2
Drum thickness, front/rear	mm in	17/17 0.7/0.7
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm in	1370 53.9

## Diesel engine

Manufacturer		DEUTZ
Model		TCD 3.6 L4
Cylinders, quantity		4
Power ISO 14396, kW/PS/rpm		74,4/101,2/2200
Power SAE J1349, kW/HP/rpm		74,4/99,7/2200
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		DOC-DPF-SCR

## Travel drive

Speed, infinitely variable	km/h mph	0 - 10,6 0.0 - 6.6
Regulation, infinitely variable		HAMMTRONIC
Gradeability, with/without vibration	%	43/48

## Vibration

Vibration frequency, front, I/II	Hz vpm	42/50 2,520/3,000
Vibration frequency, rear, I/II	Hz vpm	42/50 2,520/3,000
Amplitude, front, I/II	mm in	0,68/0,44 .027/.017
Amplitude, rear, I/II	mm in	0,68/0,44 .027/.017
Centrifugal force, front, I/II	kN lbs	84,13/77,77 18,929/17,498
Centrifugal force, rear, I/II	kN lbs	84,13/77,77 18,929/17,498

## Steering

Swing angle +/-	°	4
Steering, type		All-wheel, analogue

## Water-sprinkling system

Water sprinkling, type		Pressure
------------------------	--	----------

## Tank capacity/filling capacity

Fuel tank, capacity	L Gal	160 42.3
AdBlue/SCR reducing agent tank, capacity	L Gal	20 5.3
Water tank, capacity	L Gal	810 214.0

## Sound level

Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	105

## EQUIPMENT

2 x water pumps | Folding scraper | Easy Drive operating concept | ECO mode | Cup holder | Viewing pane, front and rear | Water filter system (3-fold) | Central water outlet | Camera system | Working spotlights

## OPTIONAL EQUIPMENT

Heating and air-conditioning system | Seat belt monitoring device | Tachograph | Bluetooth interface for Smart Doc | Smart Compact | Weather station | Dashboard cover | Edge pressing and cutting equipment | Chip spreader | HAMM Compaction Meter (HCM) | Automatic engine stop | HAMM Temperature Meter (HTM) | Back-up alarm | JDLink | Drum edge lighting | Drum lighting | Coming Home function